



ELEVATION SERIES CUBE ICE MAKER

CIM0530/O535

Ice-O-Matic
Ice. Pure and Simple

Model:

☐ CIM0530

☐ CIM0535



Energy Star Certified
on certain models

CIM0530
ON B55



Safelce

*Available for factory or field install

Features and Benefits

- 30" (768 mm) wide space-saving design.
- Produces up to 586 lbs (266 kg) of ice per day.
- *Energy and Environment*
 - Exceeds 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Safelce Purification System is an add-on option for CIM machines that destroys Coronavirus, Flu, Odors, Mold and other biological contaminants, increasing the life of the machine by up to 30%.



<https://www.youtube.com/watch?v=toReJT8QG6A&t=7s>

Ice Form

FULL CUBE DIMENSIONS	
W x D x H (in.)	7 $\frac{1}{8}$ x 7 $\frac{1}{8}$ x 7 $\frac{1}{8}$
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (in.)	3 $\frac{1}{8}$ x 7 $\frac{1}{8}$ x 7 $\frac{1}{8}$
W x D x H (mm)	10 x 22 x 22



CUBE

Bin Chart Kits for Combining Wider Bins with Smaller Models

ICE STORAGE BINS											
	Model No. Capacity Width	B25 242 lbs (110 kg) 30 in (762 mm)	B40 344 lbs (156 kg) 30 in (762 mm)	B42 351 lbs (160 kg) 22 in (559 mm)	B55 510 lbs (232 kg) 30 in (762 mm)	B700 680 lbs (308 kg) 30 in (762 mm)	B110 854 lbs (388 kg) 48 in (1,219 mm)	B1000 1,000 lbs (454 kg) 48 in (1,219 mm)	B1300 1,320 lbs (599 kg) 48 in (1,219 mm)	B1325 1,325 lbs (601 kg) 60 in (1,524 mm)	B1660 1,660 lbs (753 kg) 60 in (1,524 mm)
Kits		Kit Not Required		N/A	Kit Not Required		BPF-1	Hold Down Securement Recommended			
	CIM0530										
	CIM0535										

*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM0530	IFQ1-XL	IOMQXL (1)
CIM0535		

Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.

Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts
Evaporator (when enrolled in our filter program)	7 YEARS parts and labor

CIM0530/O535 CUBE ICE MAKER





ELEVATION SERIES CUBE ICE MAKER

CIMo530/o 535



Ice-O-Matic
Ice. Pure and Simple

Air Cooled

Please note: air-cooled units require 6" (152 mm) clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".


Dual Exhaust for Installation Flexibility



Air Cooled

Water Cooled/Remote Cooled

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8" (remote).
- E. Condenser water in, 3/8" FPT (water only).
Discharge line, 1/2" male quick connect coupling for precharged line set (remote only).
- F. Condenser water out, 1/2" FPT (water only).
- G. Liquid line, 3/8" male quick connect for precharged line set (remote only).



Water Cooled/Remote Cooled


Operating Requirements

MINIMUM		MAXIMUM	
		60 Hz	50Hz
Ambient Temp. Range Air	50°F (10 °C)	100 °F (38 °C)	110 °F (43 °C)
Water Temp.	40°F (4.4 °C)		
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5,5 BAR)	

Dimensions

ALL MODELS	
W x D x H (in.)	30.25 x 24.25 x 21.25
W x D x H (mm)	768 x 616 x 540

Specifications

Model Number	Cond. Unit	Ice Production per 24hrs		Water Usage gallons per 100 lbs of Ice 90°F air/70°F water		kWH Used per 100 lbs of ice @ 90°F air/ 70°F water	Voltage Characteristics	Min. Circuit Ampacity	Max Breaker Size	Approx. BTUs per hour
		70°F air/ 50°F water lbs (kg)	90°F air/ 70°F water lbs (kg)	Potable	Condenser					
 CIMO530A	Air	561 (254)	420 (190)	19.9	N/A	5.5	115/60/1	17.8	30	6,252
CIMO530R**	Remote	570 (259)	405 (183)	19.6	N/A	6.3		20.1		
CIMO530W	Water	586 (266)	470 (213)	20.0	181	4.7		17.4		
CIMO535A	Air	529 (240)	425 (193)	20.0	N/A	6.1	220-240/50/1	11.2	16	
CIMO535R***	Remote	500 (227)	400 (181)	20.0	N/A	6.3		12.0	20	
CIMO535W	Water	531 (241)	476 (216)	19.5	190	5.0		11.0	16	
CIMO535A-49	Air	522 (237)	416 (189)	18.0	N/A	5.9		11.2		

* Daily ice production based on half cube configuration. When installing a CIM on a drink dispenser, the **KCUBEDISP** MUST be used.

** Remote model **CIM0530R** requires the **RCA-100 1** remote condenser with optional grill guard kit.

*** Remote model **CIM0535R** requires the **RCA-106 1** remote condenser with optional grill guard kit.

Number of Wires: 3 (including ground)

Approx. Shipping Weight lbs (kg): CIM0530A 155 (70.3) • CIM0530R 160 (72.5) • CIM0530W 155 (70.3) • CIM0535A 155 (70.3) • CIM0535R 160 (72.5) • CIM0535W 155 (70.3)

REFRIGERANT:

Models ending in -49 are R449A, all other models are R404A
CIM0535A = R404A • CIM0535A-49 = R449A